

**UNITED STATES PATENT APPLICATION**

of

**James A. Baldwin**

**James A. Lundblad**

and

**Louis F. Coffin**

for

**SYSTEMS FOR RECEIVING AND PROCESSING DIGITAL DATA  
CARRIED BY SATELLITE TRANSMISSIONS**

**WORKMAN, NYDEGGER & SEELEY**

A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

## **BACKGROUND OF THE INVENTION**

### **1. The Field of the Invention**

The present invention relates to systems for receiving and processing digital transmissions at a set top box. More particularly, the present invention relates to systems and methods for processing the digital data including interactive content and digital programming content carried by digital satellite transmissions and signals.

### **2. Background and Related Art**

Set top boxes, such as satellite receivers and cable boxes, are common components of home entertainment systems and are typically used to view the programming content that is contained in digital transmissions. In most satellite and cable systems, the set top boxes typically receive digital transmissions from a head end such as a satellite. The digital data included in digital transmissions includes audio data packets, video data packets and data packets. Set top boxes are primarily designed to handle the audio and video data packets, but the architecture of most set top boxes makes this process inefficient. In addition, effectively receiving and processing the data packets is more difficult, especially when the source of the data packets delivered by the satellite and cable systems is the Internet.

In general, most satellite and cable systems are primarily concerned with transmitting the digital transmission or signal from a head end to a destination and with ensuring that the set top boxes that ultimately receive the digital transmission or signal are authorized to decrypt, if necessary, and view the content or programming of the digital transmission. As a result, adding the capability of accessing the Internet or other computer networks, which often provide interactive content, through set top boxes such as satellite receivers and cable boxes has proven both difficult and costly. The general solution has

1 been to simply have two separate set top boxes, where one of the set top boxes is primarily  
2 dedicated to processing the interactive content carried in the digital transmission.

3 The difficulty of accessing the Internet or other computer network through set top  
4 boxes such as satellite receivers and cable boxes is evident in the design and architecture of  
5 those set top boxes, which have several components that perform specific functions. In the  
6 case of the satellite receiver, the digital satellite transmission is initially received by a tuner  
7 and a demodulator, which function to select a transport stream within the digital  
8 transmission of the satellite system. Next, the transport stream is received by a  
9 demultiplexor which effectively filters the transport stream to isolate a channel that contains  
10 related audio and video packets. At this point, the satellite receiver determines whether or  
11 not the satellite receiver is authorized to decrypt the demultiplexed channel. After the  
12 channel has been decrypted, the audio and video components of the channel are decoded to  
13 produce video and audio outputs that are interpreted by a user device such as a television. If  
14 the channel is not encrypted, then decryption is obviously not necessary and the audio and  
15 video components are simply decoded.

16 As described, a typical satellite receiver includes several separate components.  
17 Some of these components require memory to operate and are often controlled or managed  
18 by a processor. A significant problem is that each component typically has its own separate  
19 memory. In other words, a typical satellite receiver may have physically separate memory  
20 chips for each component and each separate memory is only accessible by a particular  
21 component. This type of memory arrangement is costly to the consumer and does not use  
22 memory effectively. Another significant problem with satellite receivers is that the  
23 processors found in typical satellite receivers are not suited for processing interactive  
24

content and do not provide adequate browsing capabilities. As a result, using satellite receivers to access the Internet results in a poor user experience.

Another disadvantage of many set top boxes such as satellite receivers and cable boxes is that they each contain multiple processors. One of the processors is typically responsible for managing the demultiplexed channel. The other processor often handles the processing requirements associated with separating a channel from the transport stream. Neither processor is capable of effectively processing the digital data packets and having an extra processor simply increases the cost of the satellite receiver.

An inadequate solution for accessing the Internet is to couple an additional set top box with the satellite receiver. The additional set top box receives the demultiplexed channel into an essentially separate system that has the capability of performing tasks associated with Internet access and processing the digital data or interactive content. While this design may overcome the limitations of the satellite receiver with regard to processing interactive content, other problems are evident. For instance, it is immediately noticeable that the cost of the overall system increases because a consumer will be required to purchase both a satellite receiver and a set top box. In other words, the consumer is effectively purchasing two memories and two processors in the satellite receiver plus an additional processor and memory in the set top box. Thus, the architecture of current set top boxes does not allow for efficiently processing digital transmissions including digital data packets.

## SUMMARY OF THE INVENTION

The present invention relates to an architecture or system that allows the digital data transmitted across digital transmission systems, including satellite and cable systems, to be effectively processed. The systems and methods of the present invention permit a set top box such as a satellite receiver or a cable box to process interactive content and digital audio and video programming such as Moving Pictures Expert Group (MPEG) video and audio. The advantages of the present invention include reduced cost to the consumer and simpler debugging of the digital transmission system when an error occurs. Significantly, the memory of such systems is unified rather than disjointed, which reduces not only the amount of memory required by the set top box, but also the cost of the system. The unified memory may be more efficiently used by the various components of the integrated architecture when processing digital data.

A single processor included in the set top box reduces cost by eliminating one of the processors that have been previously used in prior systems and allows the set top box to process both digital programming content and interactive content. The centralized processor provides control functionality to various components of the set top box. The processor is powerful enough to handle the processing required for digital programming content as well as the processing required for web browsing, interactive content, and multimedia content. The processor is in communication with all components of the set top box that require a processor, and the processor manages a unified memory that is shared among those components of the system that require memory. The unified memory eliminates the need for separate memories and allows the memory to be used more flexibly by the applications and components present on the set top box.

1 The set top box can be equipped with multiple tuning components, which provides  
2 the ability to simultaneously process more than one channel carried by the digital  
3 transmission. By processing multiple channels, the user is able to more effectively use the  
4 content provided over the digital satellite system. This enables the user to experience  
5 additional or advanced functions, such as picture in picture. Finally, the systems of the  
6 invention can ensure that the security systems or conditional access systems required by  
7 satellite system providers remain intact and are secure.

8 Many of the functions previously performed by hardware components, such as audio  
9 decoding, video decoding, and transport functions, are performed by software in some cases,  
10 which further reduces both the necessary hardware components and their associated cost.

11 Additional features and advantages of the invention will be set forth in the  
12 description which follows, and in part will be obvious from the description, or may be  
13 learned by the practice of the invention. The features and advantages of the invention may  
14 be realized and obtained by means of the instruments and combinations particularly pointed  
15 out in the appended claims. These and other features of the present invention will become  
16 more fully apparent from the following description and appended claims, or may be learned  
17 by the practice of the invention as set forth hereinafter.

**BRIEF DESCRIPTION OF THE DRAWINGS**

In order that the manner in which the above-recited and other advantages and features of the invention are obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 illustrates exemplary components of a system used to receive and process digital transmissions;

Figure 2 illustrates a block diagram of a system for processing digital data carried by a digital transmission that includes a single processor and a unified memory;

Figure 3 is functional block diagram of a set top box and illustrates the components that permit digital transmissions or signals carrying both programming content and interactive content to be processed; and

Figure 4 is a detailed block diagram of one embodiment of a set top box architecture capable of processing multiple channels included in a digital transmission.

1                   **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

2                   As used herein, “interactive content” refers to data or information that is present on  
3 or accessed through a computer network such as the Internet and includes, but is not limited  
4 to: web pages; Hyper Text Markup Language (html) content; video content and files;  
5 graphics such as graphics interchange format (GIF) files and joint photographic experts  
6 group (JPEG) files; audio content and files; active server pages; moving pictures experts  
7 group (MPEG) audio and video files; web portals; multimedia content, internet sites and the  
8 like. Interactive content also refers to the actions that occur between an end user and the  
9 Internet or another network including, but not limited to: sending and receiving email;  
10 downloading data; uploading data; instant messaging; online purchasing; browsing the web  
11 and the like. While the invention is discussed herein with reference to satellite systems and  
12 satellite receivers, the systems and methods of the present invention apply in other systems  
13 such as cable television systems and cable boxes.

14                   As used herein “digital data” refers to audio, video, and data packets that are  
15 transmitted via digital transmission systems including, but not limited to, satellite and cable  
16 systems. The data packets often include interactive content as described above, but can also  
17 include information related to the encryption and decryption of the audio and video packets.  
18 The digital data is not limited to any particular format or standard.

19                   An advantage of digital transmission systems such as a satellite systems is the ability  
20 to transfer digital data at high rates of speed. The high rate of speed allows a satellite or  
21 digital transmission to carry multiple transport streams, each of which contains a plurality of  
22 multiplexed channels. The transport streams include digital data or packets, which are  
23 collections of bits intended for a specific purpose and which typically have a common  
24 destination.

1 The strength of a system that uses packets to transmit data or information is that  
2 packets that have different purposes or destinations may be multiplexed. Of course, packets  
3 that are multiplexed must ultimately be separated by a device receiving the multiplexed  
4 packets. The nature of a satellite transmission system is well suited to transmit interactive  
5 content in addition to satellite television programming. The interactive content is packetized  
6 and multiplexed into the satellite transmission for ultimate use by an end user.

7 Thus, a satellite system is capable of providing a consumer with access to the  
8 Internet or other computer networks and has the advantage of transmitting data at high bit  
9 rates. A user has the potential of accessing the Internet much more quickly in comparison to  
10 other methods. However, access to the Internet or other computer network is only possible  
11 if the set top box or other receiver that receives the satellite transmission can efficiently  
12 process the programming content and the interactive content that is transmitted over the  
13 satellite system. The present invention provides a system or architecture that permits a set  
14 top box to effectively and efficiently process the digital transmission that carries digital data  
15 including interactive content, video, and audio data.

16 The invention is described below by using diagrams to illustrate either the structure  
17 or processing of embodiments used to implement the systems and methods of the present  
18 invention. Using the diagrams in this manner to present the invention should not be  
19 construed as limiting of its scope. The present invention extends to both methods and  
20 systems for integrating the functions of a satellite receiver with a system capable of  
21 interacting with a computer network such as the Internet. The embodiments of the present  
22 invention may comprise a special purpose computer such as a set top box, or a general  
23 purpose computer including various computer hardware, as discussed in greater detail  
24 below.

1           Embodiments within the scope of the present invention also include computer-  
2 readable media for carrying or having computer-executable instructions or data structures  
3 stored thereon. Such computer-readable media can be any available media which can be  
4 accessed by a general purpose or special purpose computer. By way of example, and not  
5 limitation, such computer-readable media can comprise RAM, ROM, EPROM, CD-ROM or  
6 other optical disk storage, magnetic disk storage or other magnetic storage devices, or any  
7 other medium which can be used to carry or store desired program code means in the form  
8 of computer-executable instructions or data structures and which can be accessed by a  
9 general purpose or special purpose computer. When information is transferred or provided  
10 over a network or another communications connection (either hardwired, wireless, or a  
11 combination of hardwired or wireless) to a computer, the computer properly views the  
12 connection as a computer-readable medium. Thus, any such a connection is properly termed  
13 a computer-readable medium. Combinations of the above should also be included within  
14 the scope of computer-readable media. Computer-executable instructions comprise, for  
15 example, instructions and data which cause a general purpose computer, special purpose  
16 computer, or special purpose processing device to perform a certain function or group of  
17 functions. As used here in, "set top box" extends to any apparatus or system that performs  
18 the functions disclosed herein, including units for use with television sets, units integrated  
19 with television sets, general or special purpose computers, and the like.

20           Figure 1 is a block diagram generally illustrating the major components of a system  
21 or architecture capable of receiving and processing both the digital data provided in or  
22 carried by the digital transmissions of satellite systems. An antenna 20, illustrated in Figure  
23 1 as a satellite dish, receives digital transmissions or signals from a head end or source and  
24 transmits the digital transmissions to a set top box 30. The set top box 30 receives the

1 digital transmissions of the satellite system captured by the antenna 20 and processes the  
2 digital transmission to produce both video and audio outputs. The video and audio outputs  
3 are available to be rendered through a television 22 or another end device that can render the  
4 video and/or the audio, which may be a computer monitor.

5 The set top box 30 includes a system or architecture that provides the functionality  
6 and processing power necessary to permit the audio, video and interactive content carried by  
7 a digital transmission to be effectively processed. In addition, the set top box 30 does not  
8 frustrate the security and protection schemes required by providers of satellite programming  
9 content.

10 Figure 2 is a block diagram that illustrates a general architecture of the set top box 30  
11 that receives the digital transmission. The components of the set top box 30 shown in Figure  
12 2 are a processor or processing component (CPU) 60, a tuning component 32, an  
13 audio/video/data (A/V/D) unit 70 and a unified memory 80. The tuning component 32  
14 functions to select a channel from the digital transmission of the satellite system. The  
15 selected channel can carry, for example, programming content including related audio and  
16 video packets that are rendered as a television program or movie. When the selected  
17 channel is programming content, the selected channel may also carry data packets that  
18 provide security information that the set top box uses to decrypt the programming content.  
19 Alternatively, the selected channel may contain data packets that correspond to interactive  
20 content. In this case, the CPU 60 provides browsing functionality such that the interactive  
21 content may be used.

22 The system or architecture as illustrated in Figure 2 provides significant advantages.  
23 The CPU 60 provides processing requirements for the tuning component 32 and the A/V/D  
24 unit 70. As previously described, this differs from other set top boxes, which have at least

1 one other processor for the other set top box components. The set top box 30 also provides a  
2 unified memory 80 that is able to satisfy the memory requirements of the A/V/D unit 70 and  
3 the tuning component 32 effectively. The memory 80 can be used dynamically by the  
4 A/V/D unit 70 and the tuning component 32 according to their respective needs. As  
5 described, previous set top boxes utilized a separate memory for each set top box  
6 component. The CPU 60 manages the unified memory 80 and provides each component of  
7 the set top box 30 with access to the unified memory 80. As a result, the unified memory 80  
8 is more efficiently governed by the CPU 60 and less physical memory is needed for the  
9 operation of the set top box 30.

10 Because the set top box 30 includes a single CPU 60 and a unified memory 80, some  
11 of the functions of the set top box that were previously performed in hardware can be  
12 performed in software. For example, audio and video decoding can be performed in  
13 software instead of hardware in some instances. Conditional access functions and transport  
14 functions can also be implemented in software. The CPU 60 provides the set top box 30  
15 with browsing capabilities and the A/V/D unit 70 is capable of efficiently processing the  
16 interactive content or data packets received through the set top box 30. In some instances,  
17 the A/V/D unit 70 provides the browsing capabilities to the set top box 30.

18 Figure 3 is a more detailed block diagram of set top box 30 and illustrates a more  
19 detailed architecture for the set top box 30. An important and primary function of set top  
20 box 30 is to allow an end user to view the programming content carried in the digital  
21 transmissions of satellite systems. A second function of set top box 30 is to provide for  
22 conditional access such that the providers of the programming content are assured that the  
23 programming content is only accessed or viewed by authorized consumers. A third function  
24 of the architecture illustrated in Figure 3 is to provide sufficient resources such that digital

The channel output by transport module 50 is frequently an encoded bitstream and may contain MPEG audio and video packets as well as other types of video and audio

1 signals. The channel produced by the transport module 50 is received and decoded by the  
2 A/V/D unit 70 in one embodiment, and the A/V/D unit 70 is preferably capable of decoding  
3 all necessary types of video and audio packets that are carried by digital transmissions. U.S.  
4 Patents 5,774,206 and 5,812,791, which are hereby incorporated by reference in their  
5 entirety, describe processes for decoding MPEG video and audio and are implemented in  
6 one embodiment of the A/V/D unit 70. After decoding the audio and video packets, the  
7 A/V/D unit 70 produces video and audio outputs which may be interpreted by a display  
8 device. In this manner, the set top box 30 is capable of performing the function of allowing  
9 an end user to hear and view the satellite programming content contained in the digital  
10 transmission or input signal received by the antenna.

11 The operation of the tuning and demodulating component 40, the transport module  
12 50, the A/V/D unit 70, and the conditional access 90 frequently requires the assistance of  
13 both a processor and memory. The CPU 60, which is representative of a processor or  
14 computer as described previously, is capable of providing the necessary control and  
15 processing power to the components illustrated in Figure 3. In addition, the memory 80 is a  
16 physically unified memory and provides the necessary memory requirements for the A/V/D  
17 unit 70, the transport module 50, the tuning component 32, the conditional access 90, and  
18 the CPU 60. Because the memory 80 is unified, it may provide less physical memory than  
19 would otherwise be required if each component of the set top box 30 had their own separate  
20 memory.

21 The conditional access 90 is a sub-system or component of set top box 30 that  
22 ensures that the programming content of digital transmissions is viewed only by authorized  
23 consumers. As previously described, the transport functions of transport module 50 produce  
24 a demultiplexed bitstream of related packets. Each packet is typically 188 bytes long and

1 each packet has an identifier. From the identifier, the packet can be identified as a video  
2 packet, an audio packet, data packet or another type of packet.

3 The important packets, with regard to the conditional access 90, are entitlement  
4 management message (EMM) packets and entitlement control message (ECM) packets.  
5 When an EMM or ECM or other conditional access packet is received, it is sent to the  
6 conditional access 90. Typically, the EMM and ECM packets are transmitted to the  
7 conditional access 90 after the transport module 50 produces a particular channel, because  
8 the EMM and ECM packets are usually related to the particular channel being produced by  
9 transport module 50.

10 The EMM packets inform the set top box 30 which channels or programs the user is  
11 allowed to descramble and the ECM packets contain both the title, control messages, and  
12 encrypted keys, which are used to decrypt an encrypted channel. The conditional access 90  
13 typically transmits the EMM and ECM packets to a vendor supplied card or other device,  
14 which returns the decrypted keys to the conditional access 90. The conditional access 90  
15 receives the decrypted keys, which enables the set top box 30 to decrypt or descramble the  
16 channels and other signals to which the user has authorized access. As illustrated, the output  
17 channel of the transport module 50 is decrypted by the transport functions provided by the  
18 transport module 50 and the A/V/D unit 70 then decodes the decrypted channel to produce  
19 the audio and video outputs.

20 As described, the conditional access 90 typically passes the ECM and EMM packets  
21 to an external source, such as a card 91, which has the capability of decrypting the encrypted  
22 keys carried by the ECM packets. Thus, the conditional access 90, in this embodiment, may  
23 be embodied as a port through which the relevant packets are transmitted to a card 91 or  
24 other device. In another embodiment, the conditional access 90 may be embodied as an

1 applications programming interface (API) or other type of software which has the capability  
2 of interfacing or communicating with software or hardware provided by the provider of the  
3 satellite programming content. After the keys have been decrypted in both these and other  
4 embodiments, the conditional access 90 receives the decrypted keys from the card 91 or  
5 other vendor system and the set top box 30 is able to use the decrypted keys to unscramble  
6 or decrypt the corresponding channel. The conditional access 90 is an example of security  
7 means for securing a channel and for ensuring that only authorized consumers obtain access  
8 to encrypted channels. The conditional access 90 is also an example of transmission means  
9 for providing a vendor system with conditional access packets. The conditional access 90  
10 also receives the information extracted from the conditional access packets by the vendor  
11 system. The vendor system can include both software and hardware components.  
12 Typically, the conditional access 90 provides the conditional access packets to a software  
13 portion of the vendor system. In this manner, the conditional access 90 ensures that the  
14 interests of the entities providing the programming content are preserved. While the  
15 conditional access 90 has been described in terms of ECM and EMM packets, one of skill in  
16 the art will recognize that other types of conditional access packets can be handled in a  
17 similar fashion and the systems and methods of the present invention are not limited to ECM  
18 and EMM packets. The architecture of the set top box 30 allows packets, including  
19 conditional access packets, to be accessed from various components and is not limited to a  
20 particular component.

21 The resources provided by the CPU 60, the A/V/D unit 70 and the unified memory  
22 80 permit the set top box 30 to process digital data including interactive content. More  
23 specifically, the A/V/D unit 70 allows the video and audio decoding to be moved from  
24 hardware to software, thereby eliminating some of the hardware components that would

1 otherwise be included in the set top box 30. The A/V/D unit 70 is also capable of handling  
2 graphics and other interactive content that is either downloaded from or uploaded to the  
3 Internet or another network through the set top box 30. The A/V/D unit 70 or the CPU 60  
4 provides a browser that allows access to the Internet and other computer networks. Because  
5 interactive content often requires input or other actions from a consumer, the set top box 30  
6 also includes a modem 33 or other suitable device that permits digital data that originates at  
7 the set top box 30 to be uploaded or submitted.

8 In sum, the set top box 30 has a single CPU 60, which results in less cost when  
9 compared to a system with more than one processor and also provides for simpler  
10 debugging. The CPU 60 and the A/V/D unit 70 also provide the ability to perform some  
11 decoding, including audio decoding, in software as well as some of the transport functions  
12 performed by the transport module 50. The set top box 30 has a unified memory 80, which  
13 eliminates some cost when compared to systems having separate memories. The unified  
14 memory 80 allows for memory economy among the components of the set top box 30. The  
15 A/V/D unit 70 is a sub-system or component of the set top box 30 that is designed to  
16 accommodate interactive content as well as decode the audio and video packets.

17 Figure 4 is a detailed block diagram illustrating one embodiment of a set top box 30,  
18 which also serves as a satellite receiver. The tuning and demodulating component 40 of the  
19 set top box 30 has a plurality of tuners illustrated as tuner 41 and tuner 42. Providing more  
20 than one tuner enables features including but not limited to: picture in picture; recording  
21 one channel or signal while viewing a separate channel; and viewing the video of one  
22 channel while listening to the audio of another channel. For each tuner 41 and 42 there is a  
23 corresponding demodulator in the tuning and demodulating component 40, illustrated as  
24 demodulator 43 and demodulator 44. The signal received from an antenna is provided to

1 each set of tuners and demodulators and each tuner and corresponding demodulator  
2 produces a tuned and demodulated transport stream.

3 The output signal or transport stream, as described previously, is typically a serial  
4 stream of multiplexed digital data and includes identifiable packets. Because the packets are  
5 multiplexed within the serial stream or channel, the next portion or component of the set top  
6 box 30 is the transport module 50. The transport module 50, as illustrated, provides a  
7 transport demultiplexor 51 for the transport stream 45 and a transport demultiplexor 52 for  
8 the transport stream 46. More generally, there is a corresponding transport demultiplexor  
9 for each tuner and demodulator set. It may be possible for a single transport module 50 to  
10 function for all channels output by the sets of tuners and demodulators. In some instances,  
11 the transport module 50 or various functions performed by transport module 50 are  
12 embodied in software.

13 The transport demultiplexors 51 and 52 essentially function as filters to separate or  
14 isolate a particular channel from the transport streams 45 and 46. In effect, the transport  
15 streams 45 and 46 are demultiplexed by transport demultiplexors 51 and 52. The transport  
16 streams 45 and 46 have a high bit rate and the transport demultiplexors 51 and 52 reduce  
17 that bit rate significantly by discarding unneeded packets. Typically, the packets or channels  
18 output by the transport demultiplexors 51 and 52 are still encoded and are possibly  
19 encrypted. If the channel is encrypted, the transport module 50 communicates with the  
20 conditional access 90, which passes certain access packets to the card 91. The card 91  
21 generates the decrypted keys, which are then provided through conditional access 90 to the  
22 descramblers 53 and 54, which may decrypt the encrypted packets or data as previously  
23 described.

1 In the set top box illustrated in Figure 4, the conditional access 90 is shown as being  
2 evaluated and performed at either the transport module 50 or the A/V/D unit 70. However,  
3 because the set top box 30 has a central CPU 60 and the conditional access packets are  
4 easily distributed, conditional access 90 can be invoked at other times and places. In other  
5 words, set top box 30 has the capability of receiving the conditional access packets into the  
6 memory 80. Then, the conditional access packets are passed to the conditional access 90  
7 and the requirement of evaluating whether a consumer may access a particular channel at the  
8 transport module 50 is eliminated. The conditional access 90 is preferably implemented in  
9 software.

10 An important aspect of the set top box 30 is CPU 60, which is capable of providing  
11 the control and processing requirements of the tuners 41 and 42, the demodulators 43 and  
12 44, the transport demultiplexors 51 and 52, the descramblers 53 and 54, and the A/V/D unit  
13 70. Because the CPU 60 is used by other components of set top box 30, memory 80, which  
14 is associated with and controlled by the CPU 60, is economized and more efficiently used.  
15 In comparison, previous embodiments of satellite receivers had a separate memory for each  
16 component that required memory.

17 The A/V/D unit 70 is illustrated in Figure 4 as having MPEG decoder 71, audio  
18 decoder 72 and graphics engine 73. The A/V/D unit 70 is also capable, in some  
19 embodiments, of performing the transport functions provided by transport module 50. The  
20 CPU 60, in combination with A/V/D unit 70, is further capable of handling interactive  
21 content as well as providing Internet browsing capability. Thus, set top box 30 is suited for  
22 both viewing satellite programming content and effectively accessing a network such as the  
23 Internet. The A/V/D unit 70 provides video and audio outputs which are interpreted by  
24 another device such as a television.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed and desired to be secured by United States Letters Patent is: